

DIGITUS CAT 6 U/UTP patch cord - LSZH

DK-1617-100/B
EAN 4016032388043



CAT 6 U-UTP patch cord, Cu, LSZH AWG 26/7, length 10 m, color blue

The DIGITUS® Category 6 Class E patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 6 cabling. The performance is tested up to 250 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 6, because of the transparent red colored connector.

Future-oriented standards and high-end quality for your network.

- 2x RJ45 (8P8C) connectors
- Boots with kink protection, strain relief and latch protection
- Length marking on boot
- Conductor: Copper (Cu)
- Assortment: Twisted Pair Patch Cables
- Slim Version: no
- Length: 10 m
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Category: CAT 6
- Packaging: DIGITUS Polybag
- Color: blue
- Configuration: 1:1
- Jacket: LSOH
- Shielding: U-UTP, unshielded
- Structure: 4 x 2 AWG 26/7, twisted pair

Logistics

| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
| Packaging Unit Carton | 45 | 12.10 | 36.00 | 36.00 | 27.00 | 34,992.00 |
| Packaging Unit Inside | 5 | 1.34 | 14.00 | 30.00 | 36.00 | 15,120.00 |
| Packaging Unit Single | 1 | 0.27 | 2.80 | 19.00 | 27.00 | 1,436.40 |
| Net single without Packaging | 1 | 0.24 | 1,000.00 | 1.20 | 1.30 | 0.00 |

More images:



