

DIGITUS Professional CAT 6A Keystone Module, shielded, toolfree

DN-93615 4016032293767



DIGITUS CAT 6A Keystone Jack, shielded, Re-embedded
500 MHz acc. ISO/IEC 11801:2002 AM2:2009/09, tool free connection

Quick and safe wire terminations without any special tool

The Item "DN-93615" from DIGITUS® is an unshielded CAT 6A Keystone Module with tool free installation which provides best performance and link quality for your network. The compact design allows the installation of 24 pieces in a row of 483 mm (19") 1U Panels. It is conform to Category 6A / 10GBase-T Channel, ANSI/EIA/TIA 568C.2.1:2002, ISO/IEC 11801:2002.



- | Material enclosure: Zinc diecast - Nickel plated
- | Material contacts: Phosphor bronze
- | 360° cable screen connection for enhanced EMI protection
- | Contacts coating: Nickel, gold plated 0.5 µ
- | Operating Temperature: -10°C ~+60°C (ISO/IEC 11801, ANSI/TIA/EIA 568 B.2)
- | Material PCB: FR4, UL 94V-0, multilayer 1.45 mm thickness
- | Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- | Diameter Cu-Conductor: AWG (26/1 ... 22), stranded and solid
- | RJ45 jack, female, for patch panel installatio
- | Compact form allows an installation of 24 x in 483mm (19") 1U blank Panel
- | Suitable for bracket typ DN-91410, DN-91411, DN-91412
- | Opening size acc. Keystone Standard 19.35 mm x 14.8 mm
- | Tool free cable installation via LSA stripes, color coded according to EIA/TIA 568 A & B
- | Suitable for design wall plates for several well-known switching programs e.g. Busch-Jaeger part number: 1812 or 1866EB
- | Suitable for design wall plates for switching program PEHA part number: D 600 MJ8
- | Suitable for design wall plates for switching program FELLER (CH) EDIZIOnue part number e.g.: 1183-028.FMI.F.61
- | Fits easily in wall- and floor boxes, patch panels, desk boxes through short depth
- | POE+ according to IEEE 802.3at
- | Meets requirements acc. following standards: IEC 60603-7-51, ANSI/TIA/EIA 568-C.2, IEC 60512-27-100, ISO/IEC 11801 am. 2.
- | Dimensions (HxWxD): 20,14,34 mm
- | Weight: 22 g

DIGITUS Professional CAT 6A Keystone Module, shielded, toolfree

DN-93615 4016032293767

→ Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	250	6,80	53,00	31,00	23,00	37789,00
Packaging Unit Inside	25	0,68	20,00	14,00	10,50	2940,00
Packaging Unit Single	1	0,03	2,00	8,00	11,00	176,00
Net single without Packaging	1	0,00	3,70	1,50	22,00	122,10

→ Packaging type

