

Duct Grade

Overall Foil & Braid Shielded Multi-Pair 24awg
RS485 Low Capacitance 600 V



Application

A range of 24awg low capacitance cables with a high level of screening. Provides interference free, high speed data transmission suitable for RS485 applications. These cables use outer jacket materials suitable for external and duct grade installations. Not suitable for direct burial.

Cable Design

Conductor	Stranded tinned copper wire (24awg)
Insulation	Foam Polyolefin
No. of Pairs	1 or 2
Overall Shield	Overall Aluminium/polyester tape
Drain Wire	Stranded tinned copper wire
Overall Braid Shield	Tinned copper wire braid, 90% coverage
Outer Jacket	High Density Polyethylene (HDPE)



Specification

Part Number	Formation	Nom. Ø	Weight
	No. of Pairs	mm ± 10%	kg/km
5502451THD	1 x 2 x 24 awg	6,40	54
5502452THD	2 x 2 x 24 awg	8,00	79

Duct Grade

Overall Foil & Braid Shielded Multi-Pair 24awg

RS485 Low Capacitance 600 V

Electrical Characteristics

Capacitance (core/core)	42	pF/m
Capacitance (core/core/screen)	75,5	pF/m
Electrical Resistance (nom.)	82	Ohm/km
Impedance (nom.)	120	Ohm
Velocity of Propagation (nom.)	66	%

Belcom Cables Ltd. ("Belcom") reserves the right to make changes to the product described in this specification without prior notice. Belcom does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact product details can be confirmed at point of enquiry.