



**Product:** [70009PU](#)

DataTuff® 5E, 1Q #22 Str TC, PO ins, F/B, PUR HF jkt, PROFINET type C, 2M torsion

[Request Sample](#)

## Product Description

DataTuff® 5E, 1 Quad AWG 22 Tinned Copper - Stranded, Polyethylene insulation, SF/UTP - Overall Braid + Foil shielding, PUR Halogen Free jacket , PROFINET type C, 2M torsion

## Technical Specifications

### Product Overview

Suitable Applications:	PROFINET Cat5e, harsh environment, IIoT, factory or process automation, IP cameras and devices, data communication, etc.
------------------------	--

### Construction Details

#### Conductor

Size	Stranding	Material	No. of Pairs	No. of Elements
22 AWG	19x0.15 mm	TC - Tinned Copper	2	4

#### Insulation

Material	Nom. Insulation Diameter	Color Code
PE - Polyethylene	1.55 mm (0.0610 in)	White & Blue & Yellow & Orange
		1 Quad

#### Cable Core

Description
1 quad with center filler

#### Inner Jacket

Material	Nom. Diameter
TPE - Thermoplastic Elastomer	4.3 mm (0.17 in)

Table Notes:	Bedding
--------------	---------

#### Outer Shield

Shield Type	Material	Coverage
Tape	Bi-Laminate (Alum+Poly)	100%
Braid	Tinned Copper (TC)	85%

#### Outer Jacket

Separator	Material	Nom. Diameter
non-Woven Tape	PUR - Polyurethane (Halogen Free)	6.5 mm (0.26 in)

Table Notes:	Sheath Resists Weld-Splatter
Overall Cable Diameter (Nominal):	6.5 mm (0.26 in)

### Electrical Characteristics

#### Electricals

Max. Conductor DCR	Nom. Characteristic Impedance
57.1 Ohm/km	100 Ohm

#### Delay

Max. Delay	Nom. Velocity of Prop.
530 ns/100m	68%

#### High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. SRL (Structural Return Loss) [dB]
1	2.1 dB/100m	65	62	64	61	
4	4 dB/100m	56	53	52	49	23
10	6.3 dB/100m	50	47	44	41	25
16	8 dB/100m	47	44	40	37	25
31.25	11.4 dB/100m	43	40	34	31	23.6
62.5	16.5 dB/100m	38	35	28	25	21.5
100	21.3 dB/100m	35	32	24	21	20.1

Table Notes: Reference standard: ISO/IEC 11801 ed 2.0, Cat 5e

#### Transfer Impedance

Frequency	Max. Transfer Impedance
10 Mhz	Max. 10 mOhm/m

#### Voltage

Voltage Rating
300 V

## Mechanical Characteristics

#### Temperature

Operating	Installation	Storage
-40°C to +80°C	-5°C To +60°C	-40°C to +80°C

#### Trailing/Flexing Properties

Motion	Number of Cycles	Radius	Speed	Acceleration	Traverse Length	Torsion Angle
Trailing/Bending	2,000,000	60 mm	3 m/s	3 m/s <sup>2</sup>		
Torsion/Twisting	2,000,000				1 m	180 °

#### Bend Radius

Stationary Min.
30 mm (1.2 in)

## Standards and Compliance

Environmental Suitability:	Indoor, Indoor, Sunlight Resistance, Oil Resistance
AWM Compliance:	AWM 20549
Data Category:	Category 5e
ISO/IEC Compliance:	ISO/IEC 11801-1
European Directive Compliance:	EU CE Mark

## History

Update and Revision: Revision Number: 0.267 Revision Date: 04-29-2024

## Part Numbers

#### Variants

Item #	Color	Putup Type	Length	EAN
70009PU.01500	Green	Reel	500 m	8719605009470

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.