

*Armoured RG11A/U LSZH
MUD Resistant NEK606*



Application

Armoured RG11 A/U Coaxial cable designed for DATA and video signal transmission for ship- and offshore applications where mechanical protection is required.

Electrical data in compliance with MIL C-17F. The inner cable meets DNV approval and further finished to meet environmental / mechanical requirements.

Cable Design

Conductor	Tinned copper 7×0,40mm
Dielectric	Low density polyethylene Ø 7,25 ± 0.18 mm
Screen	Aluminium/polesther/aluminium tape
Braid	Bare copper braid (coverage 96%)
Inner Jacket	FR-LSZH SHF-1 < UV Resistant> Ø 10,30 mm nom.
Armour	DataGuard [®] Galvanised Steel Wire Braid (GSWB)
Outer Jacket	MUD-Resistant compound < UV Resistant>
Diameter	Ø 13,70 mm nom.
Weight	286 kg/km

*Armoured RG11A/U LSZH
MUD Resistant NEK606*

Environmental and Fire Characteristics

Degree of acidity of gases	IEC 60754-1, IEC 60754-2
Halogen acid gas	IEC 60754-1, IEC 60754-2
Smoke Emission	IEC 61034-2, EN 50268-2
Toxicity of evolved gas	EN 50305 9.2
Flame retardant	IEC 60332-1-2
Fire retardant	IEC 60332-3-22 Cat.A
UV resistant	ASTM-D-2565-92A
MUD Resistant	NEK TS 606

Performance

Impedance	75±3	Ohm
Capacitance	67±3	pF/m
Velocity ratio	66	%
Inner conductor resistance @ 500V	20,5 ± 1,5	Ohm/km
Braid resistance @ 500V	4,4 ± 1,5	Ohm/km
Spark tension of the sheath	5,5	kV
Storage Temperature	-20 to +60	°C
Installation Temperature	0 to +50	°C
Operating Temperature	-30 to +70	°C
Min. Bend Radius Installation	10/20	x Ø
Min. Bend Radius Operating	5/15	x Ø

*Armoured RG11A/U LSZH
MUD Resistant NEK606*

Attenuation

MHz	5	10	50	100	200	300	500	600	800	1000	1350	1500	1750	2150	2250	2500	2750	3000
dB	1,4	2,0	5,0	7,2	10,5	13,0	17,1	19,0	22,4	25,5	30,4	32,5	35,6	40,9	41,6	44,1	46,5	50,1

Return Loss (IEC61196-1-113)

MHz	30 - 300	300 - 600	600 - 1000	1000 - 2000	2000 - 3000
dB	> 27	> 27	>23	>18	>16

Other standards of reference

IEC 60092-370	Electrical installations in ships: Guidance on the selection of cables for telecommunication and data.
DNV TAP 827.10/20	Type Approval Program - coaxial cables
MIL-C-17	General specification for radio frequency coaxial cables
IEC61196-1	Coaxial communication cables
EN 50290-2-23	Insulation materials for telecommunication cables

Specification

Part Number	Type
AX011-WBZFM	Armada® Armoured RG11A/U Cable for the Marine environment. MUD-Resistant.