

DIGITUS Modular High Density Patch Panel, shielded

DN-91424
EAN 4016032343318



Modular Patch Panel, shielded, 48-port label field, 1U, rack mount, black RAL 9005

The DIGITUS® 48 Port 1U Modular Patch Panel ensures a High Density with the benefit of 48 Keystone Jacks in just one height unit.

- Layout Keystone Entry: Straight
- Area of application: 483 mm (19") cabinet
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
- Suitable for 483 mm (19") cabinet mounting
- Suitable for shielded Digitus® Keystone Modules and Couplers
- Central ground connection
- Plastic label field
- Technical properties:
- Housing material: 1.5 mm SPCC cold rolled steel sheet, powder-coated

- Material standard: EN 10 130(1991), BS 1449, NFA 36/401, DIN 1623, UNI 5866, UNE 36-086, SIS, JIS G 3141, ASTM, SAE, NFA 36/401
- Grounding bar material: Galvanized steel
- Physical properties:
- Operation temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)
- Operation temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)
- Colour: Black RAL9005
- Color: black, RAL 9005
- Units: 1
- Category: CAT 6A
- Ports: 48

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 15 | 8.80 | 53.00 | 28.00 | 34.00 | 50,456.00 |
| Packaging Unit Inside | 1 | 0.59 | 5.00 | 53.00 | 18.00 | 4,770.00 |
| Packaging Unit Single | 1 | 0.59 | 5.00 | 53.00 | 18.00 | 4,770.00 |
| Net single without Packaging | 1 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |

More images:

