

BNC 50Ω

Crimp Plugs and Accessories



The BNC is a bayonet style connector allowing for quick connect and disconnect with a positive locking mechanism. With a classic, dependable design, BNCs are suited to accommodate a large variety of RG and industry standard cables, in a variety of termination styles.

Nickel body, brass pin.

Specification

Part Number	Suits Cable Types	Tool Kit	Crimp Tool	Crimp Hex. Ferrule		Crimp Hex. Contact		Stripping Dimensions (mm)			Die Set	Crimp Group
				mm	inch	mm	inch	A	B	C		
BNC1C174	RG174	TL-9600	TL-6347	5.41mm	0.213"	1.73mm	0.068"	8.5	4	3.5	3D,3D2,3C,3A	A
BNC1C58	RG58,UR-M43,URM76	TL-9600	TL-9571	5.41mm	0.213"	1.73mm	0.068"	8.5	4	3.5	3D,3D2,3C,3A	A
SS-B50PA	RG58,UR-M43,URM77	TL-9600	TL-9571	5.41mm	0.213"	1.73mm	0.068"				3D,3D2,3C,3A	A
BNC1C223	RG223	TL-9600	TL-9571	5.41mm	0.213"	1.73mm	0.068"	8	5	4	3D,3D2,3C,3A	A
BNC1C213	RG213,URM67	TL-9600	TL-9571	10.9mm	0.429"	2.54mm	0.1"	4	6.2	15.3	3K, 1384	C
SS-B50PC	RG213,URM67,RG214	TL-9600	TL-9571	10.9mm	0.429"	2.54mm	0.1"				3K, 1384	C
BNC1C195	195502/195504 LMR195	TL-9600	TL-6347	5.41mm	0.213"	1.73mm	0.068"	8.5	4	3.5	3D,3D2,3C,3A	A
BNC1C240	240502/240504 LMR240	TL-9600	TL-6347	6.48mm	0.256"	1.73mm	0.068"	8	5	4	3A,3A4,3C,3D,3D2	B
BNC1C400	400502/400504 LMR400			10.9mm	0.429"	3.0mm	0.118"	9	0	4	3K52	D
SS-B50PD	400502/400504 LMR401			10.9mm	0.429"	3.0mm	0.118"				3K52	D

