



TM1S6-C Cable Tie Mount, Natural, PA 6.6, Screw, 0.51x0.32", PK100

TM1S6-C

Panduit TM1S6-C Screw Applied Cable Tie Mounts offer a through hole in the mount in which a screw or rivet can be secured, this offers maximum stability for cable bundles. Install with a #6 (M3) screw. For indoor use and are suitable for miniature, intermediate and standard cross-section cable ties. Made of Nylon 6.6. They are 0.32" (8.1 mm) wide, are natural in color and come in packages of 100.

Specifications

Material Description	Nylon 6.6
Product Type	Cable Tie Mount
Application	Low Profile Cable Tie Mount to Keep Bundle Close to Mounting Surface and for Indoor Use
Color	Natural
Environment	Indoor
Material	Nylon 6.6
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Mount Method	Screw-On
Mounting Hole Thread Size	#6
Overall Length (In.)	0.51
Overall Length (mm)	13
Overall Width (In.)	0.32
Overall Width (mm)	8
Overall Height (In.)	0.23
Overall Height (mm)	5.8
Standards Met	CE Compliant, UL Recognized:E136577, RoHS Compliant
For Use With	Miniature Cross-Section Ties

Packaging Detail

UPC	07498358160
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0266
Std. Ctn. Qty.	500
Std. Ctn. Volume (cf)	0.1329